

the ends of the attachment (7), a complete loop in which the casing (1) may be inserted and held in place by contact of the flexible element (5) on its circumference.

2. (original) The watch as claimed in claim 1, characterized in that the ends of the flexible element (5) are fastened in at least one guide (4a, 4b) inserted in the attachment (7) or in at least one of the casing supports (2a, 2b).

3. (currently amended) The watch as claimed in ~~claim 1 or 2~~ claim 1, characterized in that the casing supports (2a, 2b) have an outer part (12) for insertion of the rings (6a, 6b) of the bracelet (7), and an inner part (11) on which the casing (1) rests.

4. (original) The watch as claimed in claim 1, characterized in that the attachment (7) is integral with an internal profiled part that receives and supports the casing (1).

5. (currently amended) The watch as claimed in ~~one of the preceding claim~~ claim 1, characterized in that the casing (1) has a rim (8) around its circumference that is inserted in a groove (13) of the support (2) which is integral with the attachment (7) or otherwise.

6. (original) The watch as claimed in claim 5, characterized in that the casing (1) has a first rim (8) around its lower circumference and a second rim (9) around its upper circumference, making the watch reversible.

7. (currently amended) The watch as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the flexible element (5) consists of a thread made of plastic.

8. (currently amended) The watch as claimed in ~~one of the preceding claims~~ claim 1, characterized in that the flexible element (5) consists of a metal thread.

9. (currently amended) The watch as claimed in ~~one of the preceding claims~~ claim 1, characterized in that it comprises two flexible elements (5) secured in at least one guide (4a, 4b) to form a complete loop.

10. (currently amended) The watch as claimed in ~~one of claims 1 to 9~~ claim 1, characterized in that the casing (1) comprises a rim (8) on opposite sides of its circumference for receiving said flexible element (5).

11. (original) The watch as claimed in claim 10, characterized in that the casing comprises a first lower rim (8) and a second upper rim (9), said rims (8, 9) extending around the entire circumference of the casing (1), in particular arranged symmetrically about a median axis (20), making the casing (1) reversible.

12. (original) An attachment for a watch as claimed in claim 1, characterized in that the said attachment (7) consists of a bracelet, the two supports (2a, 2b) and the flexible element (5) forming a complete loop, said flexible element (5) being designed to be placed on the circumference of a watch casing (1).

13. (currently amended) A casing for a watch as claimed in ~~claims 11 and 12~~ claim 11.